

Laundry Press – Air operated collar and cuff FPA6-WC



Features and benefits

- High temperature polished head, dries the fabric and gives it a flat finish
- High pressure, achieves an excellent finish
- Adjustable pressure regulator, for pressing different fabrics
- Air operated, reduces operator fatigue
- Safety two button closing, improves operator safety
- Padded buck, reduces impressions
- Adjustable release timer, simplifies the operation and ensures consistent results

Main options

- Facilities that simplify the installation
 - Integral air compressor
 - Integral steam boiler

Electrical connections	Standard	Built-in boiler	Built-in air comp.
Voltage, external boiler 208-240V 1 AC 50/60 Hz	kW	0.2	1.1
Voltage, internal boiler 208-240V 3 AC 50/60 Hz	kW	-	alt. 8.4
400-415V 3N AC 50/60 Hz	kW	-	10.4
		-	12.4
		-	15.4
		-	18.4
Steam, air and vacuum connection			
Steam	DN	15	15
Rec. steam pressure	kPa	600	600
Steam consumption	kg/h	12-13	12-13
Condensate	DN	15	15
Compressed air	DN	10	-
Rec. air pressure	kPa	700	700
Air consumption	l/min	50	50
Boiler drain (internal boiler)	DN	-	15
Shipping data			
	net, kg	300	300
	crated, kg	360	360
	boxed, kg	440	440
Dimensions in mm			
A Width		970	970
B Depth		1135	1135
C Height		1220	1220
D		1530	1530
E		1070	1070
F		780	780
G		445	445
H		190	190
I		150	150
K		505	505
L		300	300
1 Control panel			
2 Electrical connection			
3 Steam connection			
4 Condensate			
5 Air connection			
6 Boiler drain (internal boiler)			
7 Water supply (internal boiler)			

