

# Tensioning Form Finishers

## FFT-D, FFT-WC



### Features and benefits

- User-friendly control panel with display
- Pivoting control board
- Automatic finishing control with microprocessor for an elevated productivity
- 9 different work programmes for garments of any fabric and size
- Possibility to select ironing mode: automatic, semi-automatic or manual
- Rotating former (180° for FFT-D and 360° for FFT-WC) for an easy handiness of garments
- Vertical and horizontal garment tensioning for a perfect finish
- Removable front collar clamp
- Adjustable shoulders
- Automatic size adjustment
- Strong ventilation unit with air-regulation
- Possibility to exclude each of the tensioning devices according to needs
- Anti-stretching device
- Upgraded air heating system (for FFT-WC)

### Main options

- 2HP motor
- All steam iron with support and teflon shoe (standard for FFT-WC)
- Clamps for side vents (standard for FFT-WC)
- 360° rotation of the form (for FFT-D)
- Side clamps
- Electronic air regulation (FFT-WC)
- Connection with steam trap for FFT-D without iron

Electrical connections		FFT-D	FFT-WC
Voltage			
400V 3N AC 50Hz	kW(A)	1.2(10)	1.2(10)
208-240V 3 AC 60Hz	kW(A)	1.2(10)	1.2(10)
Steam, air and vacuum connection			
Steam	DN	15	15
Rec. steam pressure	kPa	500-600	500-600
Steam consumption	kg/h	15-20	20-25
Condensate	DN	15	15
Compressed air	DN	8	8
Rec. air pressure	kPa	600-700	600-700
Air consumption	l/min	40	40
Shipping data			
	net, kg	160	170
	crated, kg	180	190
Dimensions in mm			
<b>A</b> Width		620	620
<b>B</b> Depth		1020	1020
<b>C</b> Height		1575-2325	1575-2325
<b>D</b>		780-1530	780-1530
<b>E</b>		550	550
<b>F</b>		345	345
<b>G</b>		795	795
<b>H</b>		1330	1330
<b>I</b>		830	830
<b>J</b>		530	530
<b>K</b>		160	160
<b>L</b>		40	40
<b>M</b>		45	45
<b>1</b> Control panel <b>2</b> Electrical connection <b>3</b> Steam inlet <b>4</b> Condensate <b>5</b> Air inlet			

