

# Industrial Ironers

## IC64821FLF, IC64825FLF, IC64832FLF



### 4 stars Ergonomic Certification



#### Certified ergonomics

Reducing workload, easing stress, intuitive and user friendly



#### Optimum productivity

Brilliant results with optimised staffing costs maintaining strict standards of hygiene



#### Full flexibility

Multiple solutions designed for your specific needs



#### Tried & tested durability

Guaranteeing consistent results without interruption



Images shown are a representation of the product only and variations may occur.

OPTIONS & AREA CONCERNED BY THE OPTIONS FLF Model - Electric and Gas heated		Superior
<b>Manual Feeding:</b>		
Vacuum Table	To optimise the feeding and by consequence the ironing quality	Yes
<b>Folding:</b>		
Antistatic Bar	To avoid polyester to stick on the cylinder	Yes
<b>Productivity:</b>		
Dubixium	Keep the cylinder temperature always uniform and optimise the productivity	Yes
DIAMMS	Operates automatically at optimum speed whilst perfectly managing the moisture in your laundry	Yes

OPTIONS & AREA CONCERNED BY THE OPTIONS FLF Model - Steam heated		Superior
<b>Manual Feeding:</b>		
Vacuum Table	To optimise the feeding and by consequence the ironing quality	Yes
<b>Folding:</b>		
Antistatic Bar	To avoid polyester to stick on the cylinder	Yes
<b>Productivity:</b>		
DIAMMS	Operates automatically at optimum speed whilst perfectly managing the moisture in your laundry	Yes

Main specifications		IC64821FLF	IC64825FLF	IC64832FLF
Capacity*,	max. water evaporation** l/h	40/63/37	48/75/46	59/93/59
Cylinder, diameter (el, gas/steam)	mm	479/457	479/457	479/457
	length	2120	2540	3170
Ironing speed	m/min	1.5-9	1.5-9	1.5-9
Heating,	electricity	37	44	54
	steam (900 kPa)	92	110	141
	gas	Btu/h (kW)	150100(44)	177400(52)
* 50% residual moisture content cotton 180g/m <sup>2</sup> and 100% cylinder use (ISO 9398-1).				
** El/steam/gas.				

Electrical connections*		IC64821FLF	IC64825FLF	IC64832FLF
<b>Heating alternative</b>				
Electric heated 400-415V 3AC 50/60 Hz kW(A)		38 (63)	45 (80)	56 (100)
Gas heated / 208-240V 3AC 60 Hz kW(A)		2 (16)	2 (16)	2 (16)
Steam heated 400V 3 AC 50/60 Hz kW(A)		2 (16)	2 (16)	2 (16)
<b>Steam, gas and air connections</b>				
Steam	DN	20	20	20
Rec. steam pressure	kPa	900	900	900
Condensate	DN	10	10	10
Gas	DN	20	20	20
Gas pressure,	Pa	2000/2500	2000/2500	2000/2500
natural gas (G20/G25)	Pa	3700/5000	3700/5000	3700/5000
propane (G31)	ø mm	150	150	150
Air outlet	m <sup>3</sup> /h	830	950	1010
Evacuated air,	m <sup>3</sup> /h	740	880	960
gas		200	200	200
el, steam				
Pressure drop	max. Pa			
<b>Sound levels</b>				
Airborne sound level	dB(A)	73	73	73
<b>Heat emission</b>				
% of installed power, max.		3	3	3
<b>Shipping data**</b>				
Shipping volume	net, kg	1425	1530	1735
<b>Dimensions in mm A</b>	m <sup>3</sup>	7.04	8.05	9.56
Overall width				
<b>B</b> Ironing width		2785	3205	3835
<b>1</b> Control panel		2120	2540	3170
<b>2</b> Exhaust connection		<b>4</b> Condensate connection		
<b>3</b> Steam connection		<b>5</b> Electrical connection		
		<b>6</b> Gas connection		

\* Other voltages available, see installation manual.

\*\* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

