

# Tumble dryer TD6-14



### Exceptional savings and effortless use



### Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- Lint filter

The horizontal filter drawer is positioned for easy access and cleaning without the need to bend down



### Long-term savings

Innovative features to save money and time, and embrace a sustainable lifestyle

- Moisture Balance (optional) helps to stop the drying process at the right time to save on energy costs



### Pure control

Monitor your equipment and performance from anywhere, allowing to take action and to improve your business with OnE Laundry - the personal assistant for hygiene validation management, process management and revenue management (optional)



### Outstanding productivity

Dry more laundry in less time: a game-changing improvement

- Reversing drum minimizes wrinkles and drying time to get an effective and even drying performance



### Global Advanced Hygiene

Global Advanced Hygiene program package I with proven log 6 reduction II disinfection of textiles through the laundry process, fulfilling the criteria of all local approved standards

I. program is available in the standard library of gas and electric heated dryers, excluding products for specific segments where temperature is not controllable

II. log 6 reduction equals to 99,9999% viral infectivity reduction. The efficacy of reduction of SARS-CoV-2 and other pathogens in the process is confirmed by RISE (The Research Institute of Sweden) on the basis of Electrolux Professional laboratory data

## Other options

- Insulated glass door keeps the door cool on the outside and heat on the inside, so the room temperature is not affected
- Lagoon Advanced Care
- Drum Speed Control adjusts the movement of the drum to help garments move correctly for a faster drying process
- Door, front and side panels are available in stainless steel
- Connectable to booking-/payment system or coin meter
- Adaptive Fan Control - The Adaptive Fan Control adjusts the fan speed automatically to keep air flowing efficiently which will save energy and help to optimize the drying time. (Only available on electric heated machines)
- High altitude kit for gas heated tumble dryers



Images shown are a representation of the product only and variations may occur.

Main specifications		TD6-14				
Rated capacity, filling factor 1:18	kg / lb	14.2 / 31.3				
Rated capacity, filling factor 1:22	kg / lb	11.6 / 25.6				
Drum, volume	litre	255				
Drum, diameter	ømm	755				
Heating alternatives:						
El	kW	6.0 / 9.0 / 13.5				
Gas	kW / BTU/h	13.5 / 46000				
Steam at 700 kPa	kW	15.0				
<b>Consumption data<sup>1</sup></b>		El 6.0 kW	El 9.0 kW	El 13.5 kW	Gas	Steam
Total time	Min	50	35.6	25.6	27.	27.1
Energy consumption	kWh	5.5	5.7	5.8	6.5	6.8
Evaporation	g/min	115	163	226	208	214
Energy water evaporation	kWh/l	0.96	0.99	1.00	1.12	1.17

1. A rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electricheated machines	220-240V 1~	50/60	6.0	7.0	32
	220-230V 3~		9.0/13.5	10.0/14.5	32/50
	240V 3~	50/60	9.0/13.5	10.0/14.5	25/32
	380-415V 3N~		9.0/13.5	10.0/14.5	16/25
	440V 3~	50/60	9.0/13.5	10.0/14.5	16/20
	480V 3~		9.0/13.5	10.0/14.5	16/20
Gas- and Steam heated machines	115V 3~	60	9.0/13.5	10.0/14.5	16/20
		60	13.2	14.3	80
	220-240V 1~	50/60	1	1.2	10
	220-240V 3~		1	1.0	10
	380-415V 3N~	50/60	1	1.0	10
	440V 3~		1	1.0	10
480V 3~	60	1	1.0	10	

1. Total power and recommended fuse does not depend on the heating power in those cases.

Steam, gas and air connections <sup>1</sup>	TD6-14
Steam	ISO 7/1-R 1"
Steam pressure	kPa 100-1000
Steam consumption	kg/h 25
Condensate	ISO 7/1-R 1"
Gas	ISO 7/1-R 1/2"
Gas pressure, Natural gas	Pa 2000 mbar 20
Gas pressure, Propane	Pa 2800-5000 mbar 28-50
Air outlet	Ømm 200
Evacuated air, electric, 6.0/9.0 kW	m <sup>3</sup> /h 260
Evacuated air, electric, 13.5 kW	m <sup>3</sup> /h 360
Evacuated air, steam	m <sup>3</sup> /h 420
Evacuated air, gas	m <sup>3</sup> /h 360
Pressure drop, electric, 6.0/9.0 kW	Max. Pa 750
Pressure drop, electric, 13.5 kW	Max. Pa 650
Pressure drop, steam	Max. Pa 650
Pressure drop, gas	Max. Pa 650
<b>Sound levels</b>	
Sound power/pressure level at drying <sup>2</sup>	dB(A) 72/56
<b>Heat emission</b>	
% of installed power, max	15
<b>Shipping data<sup>3</sup></b>	
Weight	net, kg 22
Shipping volume	m <sup>3</sup> 2
1. Operating panel	
2. Door opening, Ø580mm	
3. Electrical connection on gas heated machines	4. Gas connection/Electrical connection on electrical heated machines
	5. Exhaust connection 0
	6. Condensate connection
	7. Steam connection

1. The default gas appliances are built for one either GN or LPG gas where shall be installed at not over than 610m (2001ft) high altitude otherwise a kit for high altitude must be installed to the machine. For the kit No. please refer to the spare parts list.

2. Sound power levels measured according to ISO 60704.

3. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Silver grey and dark blue color samples can be ordered on part number 472998313.

