

Tumble dryer

TD6-37



Exceptional savings and effortless use



Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- Lintfilter
The horizontal filter drawer is positioned for easy access and cleaning without the need to bend down
- Largedoropeningforeasyloadingandunloading
- Easyaccesstovitalpartsfromfrontandrearforsimpleservicing



Long-term savings

Innovative features to save money and time, and embrace a sustainable lifestyle with excellent water evaporation efficiency per kWh

- MoistureBalance(optional)helpstostopthedryingprocessattherighttimetosaveon energy costs



Pure control

Monitor your equipment and performance from anywhere, allowing to take action and to improve your business with OnE Laundry - the personal assistant for hygiene validation management, process management and revenue management (optional)

Outstanding productivity

- Dry more laundry in less time: a game-changing improvement
- Reversingdrumminimizeswrinklesanddryingtimetogetaneffectiveandevendrying performance with 2 full loads per hour



Global Advanced Hygiene

Global Advanced Hygiene program package with proven log 6 reductionII disinfection of textiles through the laundry process, fulfilling the criteria of all local approved standards

I. programisavailableinthestandardlibraryofgasandelectricheateddryers,excludingproductsforspecificsegmentswhere temperature is not controllable
 II. log 6 reduction equals to 99,9999% viral infectivity reduction. The efficacy of reduction of SARS-CoV-2 and other pathogens in the process is confirmed by RISE (The Research Institute of Sweden) on the basis of Electrolux Professional laboratory data



Images shown are a representation of the product only and variations may occur.

Other options

- Connectable to booking-/payment system or coin meter
- Stainless steel drum, Stainless steel front
- Fresh air intake
- Exhaust on top (Top evacuation is not available on steam heated tumble dryers)
- Insert for drying special equipment
- High altitude kit for gas heated tumble dryers

Main specifications		TD6-37			
Rated capacity, filling factor 1:18	kg / lb	37.5 / 82.7			
Rated capacity, filling factor 1:22	kg / lb	30.6 / 67.5			
Drum, volume	litre	675			
Drum, diameter	ømm	913			
Heating alternatives:					
EI	kW	32.0 / 40.0			
Gas	kW / BTU/h	42 / 143400			
Steam at 600-700 kPa	kW	46.0			
Consumption data¹		EI 32.0 kW	EI40.0kW	Gas	Steam
Total time	Min	28	23	23	22
Energy consumption	kWh	15.10	15.08	16.42	19.27
Evaporation	g/min	544	676	653	700
Energy water evaporation	kWh/l	0.98	0.98	1.07	1.26

1. Atratedcapacity1:22,100%cottonloadat50%initialmoisturedriedto0%.

Electrical connections						
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A	
Electric heated	220-240V 3~	50/60	32.0/40.0	33.5/41.5	100/125	
	380-415V 3N/3~	50/60	32.0/40.0	33.5/41.5	50/63	
	440V 3~ 480V 3~	60	32.0/40.0	33.5/41.5	50/63	
	220-240V 1/1N~	60	32.0/40.0	33.5/41.5	50/63	
Gas heated/Steam heated	220-480V 3/3N~	50/60		1.8	10	
		50/60	1	1.5	10	

1. Total power and recommended fuse does not depend on the heating power in those cases.

Steam, gas and air connections ¹		TD6-37
Steam	ISO 7/1-R	1"
Steam pressure	kPa	100-1000
Steam consumption	kg/h	65
Condensate	ISO 7/1-R	1"
Gas	ISO 7/1-R	1/2"
Gas pressure, Natural gas	Pa	2000
	mbar	20
Gas pressure, Propane	Pa	2800-3700
	mbar	28-37
	Ømm	200
Air outlet	m ³ /h	1140 / 1140
Maximum air flow, Electric 50 Hz / 60 Hz	m ³ /h	1140 / 1140
Maximum air flow, Gas 50 Hz / 60 Hz	m ³ /h	1380 / 1380
Maximum air flow, Steam 50 Hz / 60 Hz	Pa	270 / 800
Maximum static back pressure, Electric 50 Hz / 60 Hz	Pa	410 / 800
Maximum static back pressure, Gas 50 Hz / 60 Hz	Pa	900 / 1100
Maximum static back pressure, Steam 50 Hz / 60 Hz		
Sound levels		
Sound power/pressure level at drying ²	dB(A)	74/57
Heat emission		
% of installed power, max		15
Shipping data³		
Weight		
Shipping volume	net, kg	283
1. Operating panel	m ³	3.25
2. Door opening, Ø810mm	6. Condensate connection	
3. Electrical connection	7. Steam connection	
4. Gas connection	8. Lintscreen	
5. Exhaust connection		

1. The default gas appliances are built for neither GNH nor LPG gas where shall be installed at not over than 610m (2001ft) high altitude otherwise a kit for high altitude must be installed to the machine. For the kit No. please refer to the spare parts list.
 2. Sound power levels measured according to ISO 60704.
 3. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Silver grey and dark blue color samples can be ordered on part number 472998313.

