

Tumble dryer

TD6-17S

Exceptional savings and effortless use



Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- Lintfilter
The horizontal filter drawer is positioned for easy access and cleaning without the need to bend down
- Largedoropeningforeasyloadingandunloading
- Easyaccesstovitalpartsfromfrontandrearforsimpleservicing
- Simpleuseoperationalpanelswithselectionoftemperatureandtimeforeasyoperation and selection



Long-term savings

Innovative features to save money and time, and embrace a sustainable lifestyle with excellent water evaporation efficiency per kWh

- MoistureBalance(optional)helpstostopthedryingprocessattherighttimetosaveon energy costs
- ThecoinversionwithEcopowertoavoidoverdryingofthegarmentsandgetalower energy consumption



Pure control

Monitor your equipment and performance from anywhere, allowing to take action and to improve your business with OnE Laundry - the personal assistant for hygiene validation management, process management and revenue management (optional)



Outstanding productivity

- Dry more laundry in less time: a game-changing improvement
- Reversingdrumminimizeswrinklesanddryingtimetogetaneffectiveandevendrying performance with 2 full loads per hour per pocket



Global Advanced Hygiene

Global Advanced Hygiene program package I with proven log 6 reduction II disinfection of textiles through the laundry process, fulfilling the criteria of all local approved standards

I. program is available in the standard library of gas and electric heated dryers, excluding products for specific segments where temperature is not controllable

II. log 6 reduction equals to 99,9999% viral infectivity reduction. The efficacy of reduction of SARS-CoV-2 and other pathogens in the process is confirmed by RISE (The Research Institute of Sweden) on the basis of Electrolux Professional laboratory data

Other options

- Payment: coinmeter with Ecopower
The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption
- Stainless steel drum, Stainless steel front
- High altitude kit for gas heated tumble dryers



Images shown are a representation of the product only and variations may occur.

Main specifications ¹		TD6-17S			
Rated capacity, filling factor 1:18	kg / lb	16.7 / 37			
Rated capacity, filling factor 1:22	kg / lb	13.6 / 30			
Drum, volume	litre	300			
Drum, diameter	ømm	760			
Heating alternatives:					
Gas	kW / BTU/h	21 / 71700			
EI	kW	9.0 / 13.5 / 18.0			
Consumption data²		Gas	EI 9.0kW	EI 13.5kW	EI 18.0 kW
Total time	Min	21	43	29	24
Energy consumption	kWh	7.11	6.65	6.51	6.51
Evaporation	g/min	329	160	231	279
Energy water evaporation	kWh/l	1.03	0.96	0.97	0.97

1. Value per pocket.

2. At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated1	220-240V 3~	50/60	9.0	10.0	25
	380-415V 3N/3~	50/60	9.0/13.5/18.0	10.0/14.5/19.0	16/25/32
	440V 3~	60	9.0/13.5/18.0	10.0/14.5/19.0	16/20/25
	480V 3~	60	9.0/13.5/18.0	10.0/14.5/19.0	16/20/25
Gas heated1	220-480V 1/1N/3/3N~	50/60	3		10
Gas heated2	220-480V 1/1N/3/3N~	50/60	3	2.0	10

1. Perpocket.
2. Complete machine.
3. Total power and recommended fuse does not depend on the heating power in those cases.

Gas and air connections1		TD6-17S
Gas	ISO 7/1-R1	1/2"
Gas pressure, Natural gas	Pa	2000
	mbar	20
Gas pressure, Propane	Pa	2800-5000
	mbar	28-50
Air outlet Evacuated air, gas/el	Ømm	200
Pressure drop, gas/el	m3/h	600 / 600
	Max. Pa	400 / 400
Sound levels Sound power/pressure level at drying2		
Heat emission	dB(A)	76/60
% of installed power, max		
Shipping data3		15
Weight		
Shipping volume	net, kg	289
1. Operatingpanel	m3	2.03
2. Dooropening, Ø580mm		
3. Electricalconnection	4. Gasconnection	
	5. Exhaustconnection	

1. The default gas appliances are built for use on either GNH or LPG gas where shall be installed at not over than 610m (2001ft) high altitude otherwise a kit for high altitude must be installed to the machine. For the kit No. please refer to the spare parts list.
 2. Sound power levels measured according to ISO 60704.
 3. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.
- Silver grey and dark blue color samples can be ordered on part number 472998313.

