

Tumble dryer TD6-10 with heat pump



Exceptional savings and effortless use



Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- Lintfilter

The horizontal filter drawer is positioned for easy access and cleaning without the need to bend down Also user-friendly ECL Easy Clean System for lint screen and filters: less maintenance and constant high performance



Long-term savings

Innovative features to save money and time, and embrace a sustainable lifestyle with up to 60% energy saving due to the heat pump technology

- No exhaust ducting needed in installations suitable anywhere at minimal cost
- Moisture Balance helps to stop the drying process at the right time to save on energy costs



Pure control

Monitor your equipment and performance from anywhere, allowing to take action and to improve your business with OnE Laundry - the personal assistant for hygiene validation management, process management and revenue management (optional)



Outstanding productivity

Dry more laundry in less time: a game-changing improvement

- Reversing drum minimizes wrinkles and drying time to get an effective and even drying performance

Other options

- Can operate in high ambient temperatures thanks to unique water cooling system
- Reversible door hanging for a convenient laundry flow
- Silent operation



Images shown are a representation of the product only and variations may occur.

Main specifications	Rated	TD6-10
capacity, filling factor 1:22 Drum, volume		kg / lb 8.6 / 19.2
Drum, diameter		litre 190
Rated input	Consumption	ømm 680
data 1	Drying time2	kW 2.3
Energy consumption3	Evaporation	Min 51
Energy water evaporation		kWh 1.64
Energy/load of linen	Water consumption4	g/min 85
		kWh/l 0.38
		kWh/kg 0.19
		litre 0-8

1. Atratedcapacity1:22,100%cottonloadat50%initialmoisturedriedto0%.

2. Drying time for filling factor 1:44 is 31 min.

3. With ambient temperature of 22°C, 50% humidity.

4. Cooling water temperature of 22°C, water pressure 4.5 bar.

Electrical connections					
Heating alternative	Mainvoltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Machines with heat pump	320-249V3N~	50	1	2.3	10

1. Total power and recommended fuse does not depend on the heating power in those cases.

Possibility to change connection during installation, see installation manual.

Sound levels		TD6-10
Sound power/pressure level at drying 1	dB(A)	70/55
Heat emission		
Average heat emission per drying cycle used to assess ventilation need 2	kW	1.0
Shipping data 3		
Weight	net, kg	188
Shipping volume	m ³	1.20
1. Operating panel	5. Drain (cooling water)	
2. Door opening, Ø400mm	6. Water connection	
3. Electric connection		
4. Drain (condensed water)		

1. Sound power levels measured according to ISO 60704.

2. For assistance with dimensioning necessary ventilation needs, contact authorized ventilation technician. For sufficient ventilation all sources introducing heat need to be taken into account plus all other parameters effecting the ventilation need. Climate zone, building parameters, room size, etc.

3. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Silver grey and dark blue color samples can be ordered on part number 472998313.

This product contains fluorinated greenhouse gases.

- R134A: 1,350kg
- GWP1430
- CO₂ equivalent: 1,931t
- Hermetically sealed

